

RG-EW1200 1200Mbps Dual-band Gigabit Wireless Router


DATASHEET




Highlights

- Support 802.11ac wave2
- 4 Omnidirectional antennas provide strong Wi-Fi signal
- Concurrently support up to 96 devices connection
- Reyee Mesh builds up flexible multi-solutions for your network
- Easy network management at your fingertips with Reyee Router App

Highlight Features







Highlight Features

Good Helper for Your Family Management

Parental Control

Health Mode

Ruijie Cloud App allows you to manage the internet access authority of the specified terminal, including the time limit, URL blocking and black/white list setup.

Parental Control

Health Mode


The health mode limits the radiation exposure and blacks out the indicator lights for you to have a good sleep.



Concurrently Support Multiple Devices Connection

Dual-Band integration together with the MU-MIMO technology offer low interference and fast speed internet to up to 96 terminals simultaneously.





Take Control of Your Home network at Your Fingertips

Set up your home network in Reyee Router App in two minutes. More Life-time Free functions are waiting for you to Explore, Experience, Expect.



Remote Reboot



Xpress Mode



Share Network







| | Basic |
|---------------------------|--|
| Dimensions (W×D×H) | 182 mm x 120 mm x 32 mm (7.17 in. × 4.72 in. × 1.26 in. antennas not included) |
| Weight | 0.22 kg (packages not included) |
| Wi-Fi Standards | Wi-Fi 5 (802.11ac) |
| MIMO | 2.4 GHz, 2×2, MU-MIMO 5 GHz, 2×2, MU-MIMO |
| Max. Wi-Fi Speed | 2.4 GHz: 300 Mbps 5 GHz: 867 Mbps |
| Channel Width | 2.4 GHz: Auto/20/40 MHz 5 GHz: Auto/20/40/80 MHz |
| Antennas | 4 |
| Antennas Type | External Omnidirectional |
| Antenna Gain | 2.4 GHz: 5 dBi 5 GHz: 5 dBi |
| WAN Port | 1×10/100 Base-T Port |
| LAN Ports | 3×10/100 Base-T Ports |
| Recommended Users | 24 |
| Max. Users | 96 |
| Power Supply | DC 12V/0.6A |
| Power Consumption | ≤8.2W |
| Operation Frequency Bands | 802.11b/g/n: 2.400 GHz to 2.483 GHz 802.11a/n/ac: 5.150 GHz to 5.350 GHz country-speci ic restrictions apply |
| Transmit Power | Regular: CE EIRP: ≤20 dBm (2.4 GHz) ≤20 dBm (5 GHz) |
| Operating Temperature | 0 °C to +45 °C (32 °F to 113 °F) |
| Operating Humidity | 5% to 95% Noncondensing |
| Certifications | CE, RoHS |

| Wireless | | |
|--|-----------------|--|
| OFDMA | - | |
| MU-MIMO | ~ | |
| BSS Coloring | - | |
| Maximum Number of SSIDs | 6 | |
| SSID Hiding | ✓ | |
| Band Steering | ✓ | |
| Guest Wi-Fi | ✓ | |
| WPA/WPA2 | ✓ | |
| WPA3 | - | |
| Roaming | Layer 2 Roaming | |
| Blacklist | ✓ | |
| Reyee Mesh | ✓ | |
| Mesh Pairing by Hardware | ✓ | |
| Mesh Pairing by Mesh Button | ✓ | |
| Mesh Pairing by Eweb | ✓ | |
| Recommended Hop Count | ≤5 | |
| Wi-Fi Optimization | ✓ | |
| QoS (WMM) | ✓ | |
| WPS | - | |
| Transmission Power Adjustment | ~ | |
| Hardware Control of the Control of t | | |
| CPU | MT7628 | |
| Flash | 16M | |



| Hardware Control of the Control of t | | |
|--|--|--|
| RAM/SDRAM | 64M | |
| Color | White | |
| System LED Indicator | ✓ | |
| Reyee Mesh LED Indicator | - | |
| Reyee Mesh Button | ✓ | |
| Power Button | - | |
| Reset Button | ✓ | |
| DC Connector Dimensions | 5.5 mm x 2.1 mm x 10 mm (0.22 in. × 0.08 in. × 0.39 in. antennas not included) | |
| | WAN | |
| Static IP | ✓ | |
| DHCP | ✓ | |
| PPPoE | ✓ | |
| Learning PPPoE Account & Password | ✓ | |
| VLAN Tagging | ✓ | |
| LAN | | |
| DHCP Server | ✓ | |
| Client List | ✓ | |
| Static IP Assignment | ✓ | |
| Port-Based Flow Control | ✓ | |
| Features | | |
| IPv6 | ~ | |
| DDNS | ✓ | |
| IPTV | ✓ | |

| Features Features | | |
|------------------------------|--|--|
| Alarm | ~ | |
| Diagnosis | ✓ | |
| UPnP | ✓ | |
| ARP Binding | ✓ | |
| Port Mapping | ✓ | |
| DMZ Host | ~ | |
| Rate Limitation of Terminals | ✓ | |
| Hardware Acceleration | ~ | |
| MAC Address Cloning | ✓ | |
| Cloud Management | ~ | |
| Repeater Mode | ✓ | |
| WISP Mode | - | |
| | Security | |
| PPTP VPN Server | - | |
| PPTP VPN Client | ✓ | |
| L2TP VPN Client | - | |
| Parental Control | ✓ | |
| Protect TCP Flood Attacks | ✓ | |
| Protect ICMP Attacks | ✓ | |
| Protect UDP Flood Attacks | ~ | |
| System | | |
| Default Access/Password | 192.168.110.1 No Password Required by Default | |
| URL Access | ✓ | |

| System | |
|----------------|---|
| Local Upgrade | ✓ |
| Online Upgrade | ✓ |
| APP Upgrade | ✓ |
| Syslog | - |
| Backup | ✓ |
| Factory Reset | ✓ |
| Language | Chinese English Vietnamese Indonesian Thai Arabic Traditional Chinese Spanish Russian |

Package Contents

| Model | RG-EW1200 |
|-------------------|-----------|
| Wireless Router | 1 |
| Power Adapter | 1 |
| Quick Start Guide | 1 |
| Cat5e UTP Cable | 1 |



Redefine your easy network

