

TwistPort™ Adaptor for ePMP™ 2000

ADAPTOR FOR EPMP™ 2000 AP

The TwistPort™ Adaptor TPA-ADAP-e2K makes the ePMP™ 2000 series and ePMP™ Force 400 C radio compatible with all TwistPort™ Antennas. TwistPort™ Adaptors are equipped with our original quick-locking waveguide port. Connecting and disconnecting the radios with the TwistPort™ Adaptor is very simple and requires no tools.



TECHNICAL DATA

Antenna Connection	TwistPort™ - Quick-Locking Waveguide Port
Radio Connection	2x Slide-On RP-SMA
Materials	Insert - Aluminium Alloy Adaptor - UV stabilized and weather resistant ABS plastic
Flame Rating	UL 94 HB
Temperature	-40°C to +60°C (-40°F to +140°F)
Wind Survival	160 km/h (100 miles/h)
Weight	0.42 Kg (0.9 lbs) – single unit 0.52 Kg (1.1 lbs) – single unit incl. package 11.5 Kg (25.3 lbs) – carton (20 units)
Single Unit	Retail Box: 10.9 x 9.8 x 5.4 cm (4.3 x 3.8 x 2.1 inch)
20 Units	Carton Box: 36.1 x 60.9 x 32.5 cm (14.2 x 23.9 x 12.8 inch)

PERFORMANCE

Frequency Range	5180 - 6400 MHz
Polarization	Dual Linear H + V
VSWR Max	1.8
Impedance	50 Ohm

COMPATIBLE WIRELESS PLATFORMS

RF elements®	any TwistPort™ Antenna
Cambium Networks™	ePMP™ 2000 AP, ePMP™ Force 400C

PACKAGE CONTENTS

TwistPort™ Adaptor

PRODUCT DIMENSIONS

