

# RG-RAP2266 REYEE Wi-Fi 6 AX3000 Indoor Ceiling-Mount Access Point



**Kode** : RG-RAP2266

**Brand** : Ruijie - Reyee

**Jenis** : Wireless Indoor

**Harga** : Rp 1.931.000,00

RG-RAP2266 Ruijie Reyee Wi-Fi AX3000 Dual-band Round Ceiling AP. Installation With Rotating, Quick and Easy.

**\*Belum termasuk adaptor dan poe injector**

**\*Spesifikasi perangkat dijual bisa berbeda dengan yang ditampilkan karena menyesuaikan dengan regulasi di Indonesia.**

**Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.**

Penawaran Harga Spesial

 **08112039555**

## Product Highlights :

- Dual-radio performance, gigabit wireless Ceiling-mounted AP
- Capable of Reyee Mesh and 802.11K/V
- Easy installation, rotating and done
- New circular aesthetics, more in line with the hotel decoration stylex
- Powerful Standalone Portal via Ruijie Cloud



## Specification

<b>Model</b>	RG-RAP2266
--------------	------------

<b>Wi-Fi Standards</b>	Wi-Fi6 (IEEE 802.11ax) Wi-Fi5 (IEEE 802.11ac Wave 2) Wi-Fi4(IEEE 802.11n) IEEE 802.11a IEEE 802.11b/g
<b>MIMO</b>	2.4GHz: 2x2, MU-MIMO 5GHz: 2x2, MU-MIMO
<b>Max. Wi-Fi Speed</b>	2.4GHz: 574Mbps 5GHz: 2402Mbps
<b>Antenna</b>	5
<b>Antenna Type</b>	Built-In Omnidirectional
<b>Antenna Gain</b>	2.4 GHz: 3.53dBi 5 GHz: 5.15dBi Note The peak gain mentioned above refers to the gain of a single antenna.
<b>Transmit Power</b>	EIRP: ≤31dBm (2.4GHz) ≤32.7dBm (5GHz) Country-specific restrictions apply
<b>Fixed Ports</b>	1x10/100/1000 Base-T port 1xDC port 1xReset button
<b>Max. Clients</b>	512
<b>Recommended Clients</b>	110
<b>Max. SSIDs</b>	8
<b>Recommended Wi-Fi Coverage Radius</b>	2.4GHz: 40 meters 5GHz: 70 meters The Wi-Fi coverage is related to the installation environment of the access point
<b>Max. Wi-Fi Coverage Radius</b>	150 meters
<b>Operation Frequency Bands</b>	802.11b/g/n/ax: 2.400 GHz to 2.4835 GHz 802.11a/n/ac/ax: 5.150 GHz to 5.350 GHz, 5.470 GHz to 5.725 GHz, 5.725 GHz to 5.850 GHz country-specific restrictions apply
<b>Frequency Bandwidth</b>	2.4 GHz: Auto/20/40 MHz 5 GHz: Auto/20/40/80/160 MHz
<b>Roaming</b>	Layer 2 roaming Layer 3 roaming
<b>Security Mode</b>	WPA-PSK, WPA2-PSK, WPA/WPA2-PSK;
<b>Network Access Mode</b>	PPPoE Client DHCP Client Static IP

<b>Dimensions</b>	220 mm x 220 mm x 52.6 mm (8.66 in. x 8.66 in. x 2.07 in., without the mounting bracket)
<b>Installation</b>	Ceiling-Mountable
<b>Power Supplies</b>	IEEE 802.3at PoE DC 12V/2A
<b>Power Consumption</b>	≤ 18W
<b>Operating Temperature</b>	0°C to 40°C
<b>Storage Temperature</b>	-40°C to 70°C
<b>Operating Humidity</b>	5% to 95% Noncondensing
<b>Storage Humidity</b>	5% to 95% Noncondensing
<b>Port Surge</b>	+/-2kV
<b>MTBF</b>	>400000H

[Download Datasheet](#)

\* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

**URL :** <https://www.citraweb.com/produk/1067/>

**Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email [sales@citraweb.com](mailto:sales@citraweb.com)**