CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com

GWN7624 GRANDSTREAM Wall Access Point



Kode : GWN7624
Brand : Lainnya
Jenis : Wireless Indoor
Harga : Rp 1.424.000,00

The GWN7624 is an in-wall Wi-Fi access point that includes three Gigabit network ports, 2 which provide PoE, to provide internet connections and power for devices such as IP phones, computers, TVs and more.

Penawaran Harga Spesial
08112039555

- 2.03 Gbps wireless throughput and 4 Gigabit wireline ports 5GHz 4×4:4 MU-MIMO
- Supports up to 200 concurrent Wi-Fi client devices
- Advanced QoS to ensure real-time performance of low-latency applications
- Anti-hacking secure boot and critical data/control lockdown via digital signatures, unique security certificate/random default password per device
- Self-power adaptation upon auto detection of PoE or PoE+
- Embedded controller can manage up to 30 local GWN series APs;
- GWN.Cloud offers unlimited AP management; GWN Manager offers premise-based software controller

Specification

Model	GWN7624
Wi-Fi Standards	IEEE 802.11 a/b/g/n/ac
Antennas	Two 5G & two double frequency internal antennas 2.4GHz, gain 3dBi; 5GHz, gain 5dBi
Wi-Fi Data Rates	5G: IEEE 802.11ac: 6.5 Mbps to 1733 Mbps IEEE 802.11n: 6.5Mbps to 600Mbps IEEE 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps 2.4G: IEEE 802.11n: 6.5Mbps to 300Mbps IEEE 802.11b: 1, 2, 5.5, 11 Mbps IEEE 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps **Actual throughput may vary depending on many factors including environmental conditions, distance between devices, radio interference in the operating environment and mix of devices in the network*

www.citraweb.com

CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com

Frequency Bands	2.4GHz Radio: 2412 - 2484 MHz 5GHz Radio: 5180 - 5825 MHz *Not all frequency bands can be used in all regions
Channel Bandwidth	2.4G: 20 and 40 MHz 5G: 20, 40 and 80 MHz
Wi-Fi and System Security	WEP, WPA/WPA2-PSK, WPA/WPA2 Enterprise (TKIP/AES); WPA3, anti-hacking secure boot and critical data/control lockdown via digital signatures, unique security certificate and random default password per device
MIMO	2×2:2 2.4GHz(MIMO) 4×4:4 5GHz(MU-MIMO)
Coverage Range	Up to 100 meters *coverage range can vary based on environment*
Maximum TX Power	2.4G: 23dBm 5G: 25dBm *Maximum power varies by country, frequency band and MCS rate*
Receiver Sensitivity	5G 802.11a: -92dBm @6Mbps, -74dBm @54Mbps; 802.11n 20MHz: -74dBm @MCS7; 802.11n 40MHz:-71dBm @MCS7 802.11ac 20MHz: -67dBm@MCS8; 802.11ac: HT40:- 63dBm @MCS9; 802.11ac 80MHz: -59dBm @MCS9 2.4G 802.11b: -96dBm@1Mbps, -88dBm@11Mbps; 802.11g: -93dBm @6Mbps, -75dBm@54Mbps; 802.11n 20MHz: -73dBm @MCS7; 802.11n 40MHz:-70dBm @MCS7
SSIDs	16 SSIDs total, 8 per radio (2.4 Ghz and 5 Ghz)
Concurrent Wireless Clients	Up to 200
Network Interfaces	1x 10/100/1000M uplink Ethernet port with PoE/PoE+ 2x 10/100/1000M Ethernet port with PSE 1x 10/100/1000M Ethernet port
Auxiliary Ports	1 x Reset Pinhole
Mounting	In-wall mountable
LEDs	1 tri-color LED for device tracking and status indication
Network Protocols	IPv4, IPv6, 802.1Q, 802.1p, 802.1x, 802.11e/WMM
QoS	802.11e/WMM, VLAN, TOS
Network Management	Embedded controller can manage up to 30 local GWN APs GWN.Cloud offers a free cloud management platform for unlimited GWN APs GWN Manager offers premise-based software controller for up to 3,000 GWN APs
Power and Green Energy Efficiency	Support 802.3az PoE 802.3af/ 802.3at; PSE Maximum Output Per Port: 6W; Maximum Power Consumption: 25W

www.citraweb.com

Environmental	Operation: -10°C to 50°C Storage: -30°C to 60°C Humidity: 5% to 95% Non-condensing
Physical	Unit Dimension: 135mm(L)x86mm(W)x38.5mm(H)
Package Content	GWN7624 In-Wall Wireless AP, 4x Screws(KB 3.5*26) , Quick Installation Guide
Compliance	FCC, CE, RCM, IC, UKCA

Download Datasheet

* *Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat*

URL : https://www.citraweb.com/produk/1088/

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com

www.citraweb.com