

# TAP100 TELTONIKA WI-FI Access Point

**Kode** : TAP100

**Brand** : Teltonika

**Jenis** : Wireless Indoor

**Harga** : Rp 1.048.000,00



TAP100 is the Teltonika Networks Access Point, perfect for strengthening Wi-Fi coverage in small enterprise and commercial spaces. This PoE-in access point can be powered by active PoE devices via its RJ45 port and was designed with simplicity and ease of installation in mind.

**\*Spesifikasi perangkat dijual bisa berbeda dengan yang ditampilkan karena menyesuaikan dengan regulasi di Indonesia.**

Penawaran Harga Spesial

 08112039555

## Features :

- Can be powered by PoE devices via RJ45 port
- UV-stabilized plastic housing that blends in with its environment
- Integrated mounting bracket for easy ceiling setup
- Free access to RMS Management for 24 months



## Specification

<b>Model</b>	TAP100
<b>WIRELESS</b>	
<b>Wireless mode</b>	IEEE 802.11b/g/n (Wi-Fi 4)
<b>Wi-Fi security</b>	WPA2-EAP/WPA3-EAP Mixed Mode, WPA3-EAP, WPA2-PSK/WPA3-SAE Mixed Mode, WPA3-SAE, OWE, WPA-PSK/WPA2-PSK Mixed Mode, WPA2-PSK, WPA2-EAP; AES-CCMP, TKIP, Auto Cipher modes, client separation
<b>SSID/ESSID</b>	SSID stealth mode and access control based on MAC address
<b>Wi-Fi users</b>	Up to 100 simultaneous connections
<b>Wireless mesh/roaming</b>	Fast roaming (802.11r)
<b>Wireless MAC filter</b>	Whitelist, blacklist
<b>ETHERNET</b>	
<b>Ethernet</b>	1 x RJ45 port 10/100 Mbps, compliance with IEEE 802.3, IEEE 802.3u, 802.3az standards, supports auto MDI/MDIX crossover
<b>NETWORK</b>	
<b>Network protocols</b>	TCP, UDP, IPv4, IPv6, ICMP, HTTP, HTTPS, SSL v3, TLS, ARP, SSH, DHCP client, SMNP
<b>SECURITY</b>	
<b>Authentication</b>	Pre-shared key, digital certificates, X.509 certificates, TACACS+, Radius, IP & Login attempts block
<b>VLAN</b>	Tag-based VLAN separation
<b>MONITORING &amp; MANAGEMENT</b>	
<b>WEB UI</b>	HTTP/HTTPS, status, configuration, FW update, CLI, troubleshoot, event log, system log, kernel log
<b>FOTA</b>	Firmware update from server, automatic notification
<b>SSH</b>	SSH (v1, v2)
<b>SNMP</b>	SNMP (v1, v2, v3), SNMP Trap
<b>JSON-RPC</b>	Management API over HTTP/HTTPS
<b>RMS</b>	Teltonika Remote Management System (RMS)

CHARACTERISTICS	
<b>CPU</b>	Mediatek, 580 MHz, MIPS 24KEc
<b>RAM</b>	64 MB
<b>FLASH storage</b>	16 MB
<b>Connector</b>	RJ45 Socket
<b>Input voltage range</b>	44.0 - 57.0 V
<b>PoE standards</b>	802.3af PoE Class 1
<b>Power consumption</b>	< 2 W Max
<b>Ethernet</b>	1 x RJ45 ports, 10/100 Mbps
<b>Status LEDs</b>	1 x Power LED (can be turned off from web-UI)
<b>Antennas</b>	2 x Internal for 2.4 GHz Wi-Fi
<b>Reset</b>	Reboot/User default reset/Factory reset button
FIRMWARE CUSTOMIZATION	
<b>Operating system</b>	RutOS (OpenWrt based Linux OS)
<b>Supported languages</b>	Busybox shell, Lua, C, C++
<b>Development tools</b>	SDK package with build environment provided
PHYSICAL SPECIFICATION	
<b>Casing material</b>	UV stabilized plastic
<b>Dimensions (W x H x D)</b>	158 mm x 30 mm
<b>Mounting options</b>	AP Mounting Bracket (for ceiling mount)
<b>Operating temperature</b>	-40 °C to 75 °C
<b>Ingress Protection Rating</b>	IP30
<b>Operating humidity</b>	10% to 90% non-condensing
REGULATORY & TYPE APPROVALS	
<b>Regulatory</b>	CE, UKCA, CB, FCC, IC, WEEE, ANRT
SAFETY	

<b>Standards</b>	IEC 62368-1:2018 EN IEC 62368-1:2020+A11:2020 EN IEC 62311:2020
------------------	---

Standard package :

- TAP100 Access point
- 15 W PoE Injector
- QSG (Quick Start Guide)
- Packaging box

[Download Datasheet](#)

\* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

**URL :** <https://www.citraweb.com/produk/1119/>

**Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email [sales@citraweb.com](mailto:sales@citraweb.com)**

www.citraweb.com