

# FD1602S-B1 C-DATA 2PON 2GE 1SFP+ GPON OLT

**Kode** : FD1602S-B1  
**Brand** : C-Data  
**Jenis** : FTTH OLT  
**Harga** : Rp 4.150.000,00  
 Rp 7.210.000,00



GPON OLT FD1602S-B1 CDATA completely meet relative standard of ITU G.984.x and FSAN, the device with 2 uplink Ethernet ports and 1 10 Gigabit uplink port and 2 GPON port. Each GPON port supports the splitting ratio of 1:128, The GPON system supports up to 256 terminal connections.

Penawaran Harga Spesial  
 08112039555

## Specification

<b>Model</b>	FD1602S-B1
<b>Uplink Port</b>	2 x 10/100/1000M auto-negotiation Ethernet ports 1 x 10 Gigabit uplink port
<b>PON Port</b>	Quantity : 2
	Physical interface : SFP slot
	Interface type : GPON: ITU-TG.984.2 Class B+/Class C+
	Max splitting ratio : GPON: 1:128
<b>Management Port</b>	1 CONSOLE local management port
<b>Transmission distance</b>	20KM
<b>Port rate</b>	GPON: Downstream: 2.5Gbps Upstream: 1.25Gbps
<b>Wavelength</b>	Forwarding: 1490nm Receiving: 1310nm
<b>Interface type</b>	SC/UPC
<b>Fiber type</b>	9/125µm SMF (Single Mode Fiber)
<b>Light transmission power</b>	Class B+ +1.5 ~ +5dBm Class C+ +3 ~ +7dBm

<b>Receiving sensitivity</b>	Class B+ : -28dBm Class C+ : -30dBm
<b>Saturation power</b>	Class B+ -8dBm Class C+ -12dBm
<b>Backplane Bandwidth</b>	31.5G
<b>Power supply</b>	AC : 100V ~ 240V, 47~63Hz DC : External adapter mode 12V/2.5A
<b>Working temperature</b>	-15 ~ 50 C
<b>Storage temperature</b>	-40 ~ 85 C
<b>Ambient humidity</b>	5 ~ 90% (Non-condensing)

[Download Datasheet](#)

\* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

**URL :** <https://www.citraweb.com/produk/1229/>

**Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email [sales@citraweb.com](mailto:sales@citraweb.com)**