

FD1304S C-DATA 4PON 4GE 4SFP+ EPON OLT

Kode : FD1304S

Brand : C-Data

Jenis : FTTH OLT

Harga : Rp 4.150.000,00

Rp 5.350.000,00



EPON OLT FD1304S CDATA completely meet relative standard of IEEE 802.3x and FSAN, which is 1U rack-mounted device with 4 uplink Ethernet ports, 4*10GE uplink ports and 4 EPON ports. Each EPON port supports the splitting ratio of 1:64, The EPON system supports up to 256 terminal connections.

Penawaran Harga Spesial
 **08112039555**


Specification

| | |
|------------------------------|---|
| Model | FD1304S |
| Uplink Port | 4x 10/100/1000M auto-negotiation Ethernet ports 4x SFP+ 10G interfaces |
| PON Port | Quantity : 4 |
| | Physical interface : SFP slot |
| | Interface type : EPON: IEEE802.3ah Max splitting ratio : EPON: 1:64 |
| Management Port | 1 100/1000BASE-Tx out-band Ethernet port 1 CONSOLE local management port |
| Transmission distance | 20KM |

| | |
|---------------------------------|--|
| Port rate | EPON: Symmetrical 1.25Gbps |
| Wavelength | Forwarding: 1490nm Receiving: 1310nm |
| Interface type | SC/UPC |
| Fiber type | 9/125 μ m SMF (Single Mode Fiber) |
| Light transmission power | PX20+: 2~5.5dBm |
| Receiving sensitivity | PX20+:-28dBm |
| Saturation power | PX20+:-8dBm |
| Backplane Bandwidth | 98G |
| Power supply | AC : 100V ~ 240V, 47~63Hz DC : -40 ~ -72VDC |
| Working temperature | -15 ~ 50 C |
| Storage temperature | -40 ~ 85 C |
| Ambient humidity | 5 ~ 90% (Non-condensing) |

[Download Datasheet](#)

* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

URL : <https://www.citraweb.com/produk/1231/>

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com