

# FD514GD-R460 C-DATA 4GE DUAL BAND WIFI XPON ONU



**Kode** : FD514GD-R460

**Brand** : C-Data

**Jenis** : FTTH ONT/ONU/MDU

**Harga** : Rp 405.000,00

Rp 460.000,00

FD514GD-R460 CDATA is an indoor fiber broadband access terminal. The device provides one GPON / EPON adaptive optical port and supports XPON mode. It can be used in connection with our company FD16 series GPON OLT or FD11 / 12 series EPON OLT. It can also interconnect with the mainstream manufacture (Huawei / ZTE / Fiberhome) GPON or EPON OLT to provide users with Internet and WIFI services based on GPON and EPON technology.

**\*Spesifikasi perangkat dijual bisa berbeda dengan yang ditampilkan karena menyesuaikan dengan regulasi di Indonesia.**

Penawaran Harga Spesial

 08112039555

- In compliant with IEEE802.3ah and ITU - T G.984 standard
- Support ONU auto-discovery/Link detection/remote upgrade of software
- Support SN and LOID+Password multiple registration methods
- Support port VLAN configuration
- Support port-based rate limitation and bandwidth control
- Support MAC address learning
- Support MAC address learning account limit
- Support VLAN transparent/tag/translate/trunk
- Support broadcasting storm resistance function
- Support igmp transparent/snooping/proxy mode
- Support Dynamic Bandwidth Allocation (DBA)
- Support AES encryption and decryption
- EMS network management based on SNMP ,convenientfor maintenance
- Support power-off alarm function, easy for link problem detection
- Support Firewall
- Support MAC address/URL filter
- Support remote WEB/Telnet access control
- Single-fiber access, provides internet, WIFI multiple service.

## Specification

<b>Model</b>	FD514GD-R460
--------------	--------------

<b>User Port (LAN)</b>	4*10/100/1000Mbps adaptive Ethernet port Full/half duplex Auto MDI/MDI-X
<b>Indicators</b>	PWR / PON / LOS / LAN / INT / WIFI
<b>PON Mode</b>	EPON : 1000BASE-PX20+ symmetric GPON : FSAN G.984.2 standard,Class B+
<b>PON Rate</b>	EPON : 1.25Gbps (downstream/upstream) GPON : 2.488Gbps/1.244Gbps (downstream/upstream)
<b>Wavelength</b>	Transmit : 1310nm Receiver : 1490nm
<b>Receiving sensitivity</b>	EPON : -27dBm GPON : -28dBm
<b>Saturated power</b>	EPON : -3dBm GPON : -8dBm
<b>Transmitting power</b>	EPON : 0 ~ 4dBm GPON : 0.5 ~ 5dBm
<b>WIFI</b>	IEEE802.11b/g/n(2.4G) Max rate: 300M MAX TX power : 17dBm  IEEE802.11a/n/ac(5G) Max rate: 867Mbps MAX TX power : 17dBm
<b>Power</b>	External 12VDC/1A power supply adapter
<b>Power consumption</b>	≤9.7W
<b>Working temperature</b>	0 to 40°C
<b>Operating humidity</b>	10% to 90%(Non-condensing)

[Download Datasheet](#)

\* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

**URL :** <https://www.citraweb.com/produk/1234/>

**Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email [sales@citraweb.com](mailto:sales@citraweb.com)**