

FD712XW-R460 C-DATA 1GE 1FE CATV WIFI XPON ONU



Kode : FD712XW-R460

Brand : C-Data

Jenis : FTTH ONT/ONU/MDU

Harga : Rp 480.000,00

FD712XW-R460 C-DATA dual-mode ONU supports EPON and GPON two modes access. The ONU automatically switches into the corresponding PON mode by identifying the local OLT mode to complete GPON or EPON adaptive access.

***Spesifikasi perangkat dijual bisa berbeda dengan yang ditampilkan karena menyesuaikan dengan regulasi di Indonesia.**

Penawaran Harga Spesial

 08112039555

FD712XW-R460 integrates wireless function which meets 802.11 b/g/n technical standards. It has two external high gain omnidirectional antennas, the wireless transmission rate up to 300Mbps. It has the characteristics of strong penetrating power and wide coverage. It can provide users with more efficient data transmission security.

- In compliant with IEEE802.3ah and ITU - T G.984 standard
- Support ONU auto-discovery/Link detection/remote upgrade of software
- Support SN and LOID+Password multiple registration methods
- Support port VLAN configuration
- Support port-based rate limitation and bandwidth control
- Support MAC address learning
- Support MAC address learning account limit
- Support VLAN transparent/tag/translate/trunk
- Support remote CATV port management
- Support broadcasting storm resistance function
- Support igmp transparent/snooping/proxy mode
- Support Dynamic Bandwidth Allocation (DBA)
- Support AES encryption and decryption
- EMS network management based on SNMP ,convenient for maintenance
- Support power-off alarm function, easy for link problem detection
- Support Firewall
- Support MAC address/URL filter
- Support remote WEB/Telnet access control

Specification

Model	FD712XW-R460
User Port (LAN)	1x10/100 and 1x10/100/1000Mbps adaptive Ethernet port Full/half duplex Auto MDI/MDI-X
Indicators	PWR / PON / LOS / GE / FE / INT / CATV / WIFI
PON Mode	EPON : 1000BASE-PX20+ symmetric GPON : FSAN G.984.2 standard,Class B+
PON Rate	EPON : 1.25Gbps (downstream/upstream) GPON : 2.488Gbps/1.244Gbps (downstream/upstream)
Wavelength	Transmit : 1310nm Receiver : 1490nm
Receiving sensitivity	EPON : -27dBm GPON : -28dBm
Saturated power	EPON : -3dBm GPON : -8dBm
Transmitting power	EPON : 0 ~ 4dBm GPON : 0.5 ~ 5dBm
CATV (Input/Output port)	Wavelength : 1550nm Input optical power : -18dBm~0dBm(with AGC) RF frequency : 47MHz~1000MHz RF output level : 78dBuV (@-12~-2dBm@85MHz) (with AGC) RF output return loss : >12dB(with AGC) RF impedance : 75Ω
WIFI	IEEE802.11b/g/n (2.4G) Max rate : 300M (2.4G) MAX TX power 2.4G : 17dBm
Power	External 12VDC/1A power supply adapter
Power consumption	≤7.2W
Working temperature	0 to 40°C
Operating humidity	10% ~ 90% (Non-condensing)

[Download Datasheet](#)

* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

URL : <https://www.citraweb.com/produk/1236/>

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com