

FD614GD-R460 C-DATA 4GE 1POTS DUAL BAND XPON ONU



Kode : FD614GD-R460

Brand : C-Data

Jenis : FTTH ONT/ONU/MDU

Harga : Rp 455.000,00

FD614GD-R460 CDATA is an indoor fiber broadband access terminal. The device provides one GPON / EPON adaptive optical port and supports XPON mode. It can be used in connection with our company FD16 series GPON OLT or FD11 / 12 series EPON OLT.

Penawaran Harga Spesial

 08112039555

- In compliant with IEEE802.3ah and ITU - T G.984 standard
- Support ONU auto-discovery/Link detection/remote upgrade of software
- Support SN and LOID+Password multiple registration methods
- Support port VLAN configuration
- Support port-based rate limitation and bandwidth control
- Support MAC address learning
- Support MAC address learning account limit
- Support VLAN transparent/tag/translate/trunk
- Support broadcasting storm resistance function
- Support igmp transparent/snooping/proxy mode
- Support Dynamic Bandwidth Allocation (DBA)
- Support AES encryption and decryption
- EMS network management based on SNMP ,convenient for maintenance
- Support power-off alarm function, easy for link problem detection
- Support Firewall
- Support MAC address/URL filter
- Support remote WEB/Telnet access control
- Single-fiber access, provides internet, WIFI ,VOIPmultiple service.

Specification

| | |
|------------------------|--|
| Model | FD614GD-R460 |
| User Port (LAN) | RJ-45 connector 4 *10/100/1000Mbps adaptive Ethernet port Full/half duplex Auto MDI/MDI-X |
| Indicators | PWR / PON / LOS / LAN / INT / TEL / WIFI |

| | |
|------------------------------|---|
| PON Mode | EPON : 1000BASE-PX20+ symmetric GPON : FSAN G.984.2 standard,Class B+ |
| PON Rate | EPON : 1.25Gbps (downstream/upstream) GPON : 2.488Gbps/1.244Gbps (downstream/upstream) |
| Wavelength | Transmit : 1310nm Receiver : 1490nm |
| Receiving sensitivity | EPON : -27dBm GPON : -28dBm |
| Saturated power | EPON : -3dBm GPON : -8dBm |
| Transmitting power | EPON : 0 ~ 4dBm GPON : 0.5 ~ 5dBm |
| User Port (POTS) | RJ-11 connector 1*accounts SIP protocol TDMF G711U/G711A/G729/G722 encoding and decoding |
| WIFI | IEEE802.11b/g/n(2.4G) Max rate : 300Mbps MAX TX power : 17dBm IEEE802.11a/n/ac(5G) Max rate : 867Mbps MAX TX power : 17dBm |
| Power | External 12VDC/1.5A power supply adapter |
| Power consumption | ≤9.7W |
| Working temperature | 0 to 40°C |
| Operating humidity | 10% ~ 90%(Non-condensing) |

[Download Datasheet](#)

* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

URL : <https://www.citraweb.com/produk/1249/>

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com