

V2801RGW V-SOL 1XPON 1GE WIFI4 ONU


Kode : V2801RGW

Brand : V-Sol

Jenis : FTTH ONT/ONU/MDU

Harga :

1 - 19 : Rp 230.000,00

20 - ... : Rp 225.000,00

V2801RGW vsol (1GE+WiFi 4 XPON ONT) is specially designed to meet the access requirements of telecom operators such as FTTH and SOHO. The ONT is based on a high-performance chip solution (Realtek), supports mature IEEE 802.11 b/g/n WiFi 4 technology, and also supports Layer 2/Layer 3 functions, providing data services for carrier-grade FTTH applications.

1*GE+WiFi4

***Spesifikasi perangkat dijual bisa berbeda dengan yang ditampilkan karena menyesuaikan dengan regulasi di Indonesia.**

Penawaran Harga Spesial

 **08112039555**

Key Features :

- Realtek Chipset High Performance Solution
- IEEE802.3ah EPON or ITU-TG.984.X GPON Standard
- WiFi IEEE802.11b/g/n 2T2R 5dBi Antenna
- Powerful Firewall

Specification

Model	V2801RGW
PON Interface	<ul style="list-style-type: none"> • 1 XPON port(EPON PX20+ & GPON Class B+) • SC single mode, SC/UPC connector • TX optical power : 0~+4dBm • RX sensitivity : -27dBm • Overload optical power : -3dBm(EPON) or -8dBm(GPON) • Transmission distance : 20KM
Wifi Interface	<ul style="list-style-type: none"> • IEEE802.11b/g/n(TX power:17dBm/16dBm/ 15dBm), 300Mbps • Support 13 Channels
LAN interface	1*GE Auto-negotiation RJ45 ports
PON mode	XPON Dual Mode , Can access mainstream EPON/GPON OLTs

Software Mode	Routing Mode
Multicast	IGMP v1/v2/v3 , IGMP snooping
Firewall	DDOS, Filtering Based on ACL/MAC/ URL
Layer2	802.1D&802.1ad bridge, 802.1p Cos, 802.1Q VLAN
Layer3	IPv4/IPv6, DHCP Client/Server, PPPoE, NAT, DMZ, DDNS
WiFi	<ul style="list-style-type: none"> • WiFi Authentication : WEP/WAP-PSK(TKIP)/WAP2-PSK(AES) • Support : multiple SSID
Security	<ul style="list-style-type: none"> • Flow & Storm control, Loop Detection
O&M	WEB/TELNET/OAM/OMCI/TR069
Dimension	120mm×78mm×30mm(L×W×H)
Power adapter	DC 12V, 1A, external AC-DC power adaptor
Power supply	≤6W
Operating condition	Operating temp : -10 ~ +55C Operating humidity : 5 ~ 95% (non-condensing)
Storing condition	Storing temp: -40 ~ +70C Storing humidity: 5 ~ 95% (non-condensing)
Indicators	POWER, LOS, PON, LAN, WiFi

[Download Datasheet](#)

* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

URL : <https://www.citraweb.com/produk/1300/>

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com