

# RG-ES220GS-LP REYEE 20-Port Gigabit Smart Cloud Managed PoE Switch

**Kode** : RG-ES220GS-LP

**Brand** : Ruijie - Reeye

**Jenis** : Switch Managed POE

**Harga** : Rp 2.528.000,00




RG-ES220GS-LP REYEE merupakan Smart Cloud Managed PoE Switch dilengkapi dengan 18x 10/100/1000 Base-T port (16x PoE/PoE+ Out port) dan 2 SFP port. Cocok digunakan untuk kebutuhan SMB (Small Medium Business).

**Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.**

Penawaran Harga Spesial

 **08112039555**



## Specification

<b>Model</b>	RG-ES220GS-LP
<b>Product category</b>	Layer 2
<b>Ports</b>	10/100/1000 BASE-T ports : 18 port (16 port PoE/PoE+) 1GE SFP ports : 2 port
<b>Switching capacity</b>	40 Gbps (bit/s)
<b>MAC address table</b>	8000
<b>Fan</b>	Fanless
<b>Dimensions (W x D x H)</b>	300mm x 223mm x 43.6mm (11.81 in. x 8.78 in. x 1.72 in)
<b>MTBF</b>	> 200,000
<b>Max. PoE budget</b>	130 W
<b>Forwarding rate</b>	29.76 Mpps
<b>Maximum VLAN</b>	16
<b>Surge protection</b>	Service port: $\pm 6$ kV for common mode Power connector: $\pm 6$ kV for common mode and $\pm 6$ kV for differential mode
<b>Power consumption</b>	Less than 15 W with no PoE load (110 V) Less than 14 W with no PoE load (220 V) Less than 160 W with PoE full load (110 V) Less than 157 W with PoE full load (220 V)
<b>Power supply</b>	Fixed power supply. AC power supply: - Rated input voltage: 100 V AC to 240 V AC, 50 Hz to 60 Hz - Maximum input voltage: 90 V AC to 264 V AC, 47 Hz to 63 Hz - Rated input current: 3 A
<b>Operating temperature</b>	0°C to 40°C
<b>Storage temperature</b>	-40°C to +70°C
<b>Operating humidity</b>	10% to 90% RH (non-condensing)

[Download Datasheet](#)

\* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

URL : <https://www.citraweb.com/produk/1389/>

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: **0274-554444** atau email [sales@citraweb.com](mailto:sales@citraweb.com)