

# Dream Machine Pro UNIFI UBIQUITI

**Kode** : UDM-PRO

**Brand** : Ubiquiti

**Jenis** : Router Rackmount

**Harga** : Rp 8.200.000,00



**Dream Machine Pro UNIFI UBIQUITI** 10G Cloud Gateway with 100+ UniFi device / 1,000+ client support and 3.5 Gbps IPS routing. **Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.**

Penawaran Harga Spesial

 **08112039555**



## Specification

|                      |                                     |
|----------------------|-------------------------------------|
| <b>Model</b>         | UDM-PRO                             |
| <b>Processor</b>     | Quad-core ARM Cortex-A57 at 1.7 GHz |
| <b>System Memory</b> | 4 GB                                |

|                                      |   |
|--------------------------------------|---|
| <b>On-board Storage</b>              | 16 GB   |
| <b>Ports</b>                         | 1 GbE RJ45 : 9 (1G/100M/10M)<br>10G SFP+ : 2 (10G/1G)                 |
| <b>Form Factor</b>                   | Rack mount (1U)   |
| <b>Managed UniFi Devices</b>         | 100+  |
| <b>Managed Cameras</b>               | (24) HD<br>(14) 2K<br>(8) 4K  |
| <b>Managed Access Hubs</b>           | 150   |
| <b>Simultaneous Users Connected</b>  | 1,000+  |
| <b>Max. WAN Port Count</b>           | 8   |
| <b>Default WAN Ports</b>             | (1) 10G SFP+<br>(1) GbE RJ45  |
| <b>IDS/IPS Throughput</b>            | 3.5 Gbps  |
| <b>Redundancy</b>                    | Shadow Mode (VRRP) Gateway Failover<br>DC Power Backup                |
| <b>MAC Address Table Size</b>        | 4,000   |
| <b>NVR Storage</b>                   | (1) 3.5" NVR HDD bay  |
| <b>Max. Power Consumption</b>        | 33W   |
| <b>Power Method</b>                  | (1) Universal AC input, 100–240V AC, 50/60 Hz<br>(1) USP-RPS DC input |
| <b>Power Supply</b>                  | AC/DC, internal, 50W  |
| <b>Supported Voltage Range</b>       | 100–240V AC   |
| <b>Dimensions (W x D x H)</b>        | 442.4 x 43.7 x 285.6 mm (17.4 x 1.7 x 11.2")                          |
| <b>Enclosure Material</b>            | Aluminium CNC, SGCC steel   |
| <b>Mount Material</b>                | SGCC steel  |
| <b>LCM Display</b>                   | 1.3" touchscreen  |
| <b>Management</b>                    | Ethernet<br>Bluetooth   |
| <b>Button</b>                        | (1) Factory-reset   |
| <b>ESD/EMP Protection</b>            | Air: ± 15kV, contact: ± 8kV   |
| <b>Ambient Operating Temperature</b> | -10 to 40° C (14 to 104° F)   |
| <b>Ambient Operating Humidity</b>    | 5 to 95% noncondensing  |
| <b>Certifications</b>                | CE, FCC, IC, Anatel, SRRC   |

*\* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat*

**URL :** <https://www.citraweb.com/produk/1427/>

**Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email [sales@citraweb.com](mailto:sales@citraweb.com)**

[www.citraweb.com](http://www.citraweb.com)