**CITRAWEB SOLUSI TEKNOLOGI**
www.citraweb.com
info@citraweb.com
sales@citraweb.com

# FD1801S-C1 C-DATA 1 PORT COMBO XGS-PON & GPON OLT



**Kode** : FD1801S-C1
**Brand** : C-Data
**Jenis** : FTTH OLT
**Harga** : Rp 6.810.000,00
~~Rp 7.850.000,00~~

**FD1801S-C1** adalah perangkat OLT rack-mounted 1U berstandar ITU-T G.9807.1 yang dilengkapi 2 port Gigabit Ethernet dan 1 port SFP+ 10G uplink port. Pada port PON memiliki COMBO PON (1 XGS-PON & GPON) dengan split ratio 1:128.

***Belum termasuk SFP module.**

Penawaran Harga Spesial
08112039555

**Fitur :**
**- 1*Combo PON port up to 1:128 split ratio.**
**- Symmetrical 10Gbps transmission rates.**
**- Uplinks dengan 1 port SFP+ 10G dan 2 port Gigabit Ethernet.**
**- Jarak transmisi up to 20km.**

www.citraweb.com





**CITRAWEB SOLUSI TEKNOLOGI**
www.citraweb.com
info@citraweb.com
sales@citraweb.com

**Spesifikasi**

| | |
|---|---|
| **Model** | FD1801S-C1 |
| **Uplink Port** | 2* 10/100/1000M auto-negotiation Ethernet ports |
| | 1* SFP+ interfaces |
| **PON Port** | Quantity : 1 |
| | Physical interface : SFP slot |
| | Max splitting ratio : GPON: 1:128 |
| **Management Port** | 1* CONSOLE local management port |
| **Transmission distance** | 20KM |
| **Port rate** | XGS-PON:<br>Downstream: 10Gbps<br>Upstream: 10Gbps<br><br>GPON:<br>Downstream: 2.5Gbps<br>Upstream: 1.25Gbps |
| **Wavelength** | XGS-PON:<br>Forwarding: 1577nm<br>Receiving: 1270nm<br><br>GPON:<br>Forwarding: 1490nm<br>Receiving: 1310nm |
| **Interface type** | SC/UPC |
| **Fiber type** | 9/125μm SMF (Single Mode Fiber) |
| **Light transmission power** | XGS-PON&GPON COMBO<br>5~8dBm (9.953G)<br>3~7dBm (2.488G) |
| **Receiving sensitivity** | XGS-PON&GPON COMBO<br>≥-29dBm (9.953G)<br>≥-30.5dBm (2.488G)<br>≥-30dBm (1.244G) |
| **Saturation power** | XGS-PON&GPON COMBO<br>≤-8dBm (9.953G)<br>≤-10dBm (2.488G)<br>≤-12dBm (1.244G) |
| **Network Management Method** | Support CLI, SNMP, TELNET, SSH, WEB |
| **Backplane Bandwidth** | 44G |

www.citraweb.com

| | |
|---|---|
| **Power supply** | AC: 100V ~ 240V, 47~63Hz |
| | DC: External adapter mode 12V/2.5A |
| | BBU (Backup Battery Unit):<br>DC: 11V?14V. Function: When the regular power supply is cut off, it can be switchedtothebackup power supply, and when the regular power supply resumes, it will switch back to the regular power supply and charge the backuppower supply |
| **Maximum Power** | <14W |
| **Working temperature** | -15 ~ 50 C |
| **Storage temperature** | -40 ~ 85 C |
| **Ambient humidity** | 5 ~ 90% (Non-condensing) |

**Download Datasheet**

** Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat*

**URL :** https://www.citraweb.com/produk/1534/

**Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com**

www.citraweb.com