CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com

eKitEngine AP772E HUAWEI BE6450 High-Protection Dual - Band Wi-Fi 7 Gigabit Outdoor Access Point



Kode : AP772E
Brand : Huawei
Jenis : Wireless Outdoor
Harga : Rp 4.975.000,00

HUAWEI eKitEngine AP772E BE6450 High-Protection Dual - Band Wi-Fi 7 Gigabit Outdoor Access Point adalah *Access Point outdoor* berteknologi Wi-Fi 7 (802.11be) dengan dukungan hingga 6 *spatial streams* untuk menghadirkan performa nirkabel super cepat dan stabil. Memiliki ketahanan ekstrem terhadap air dan debu bersertifikasi IP68 serta proteksi lonjakan listrik yang kuat, AP ini dirancang khusus sebagai solusi ideal untuk area luar ruangan berdensitas pengguna tinggi.

***Belum termasuk adaptor dan poe injector**

***Spesifikasi perangkat dijual bisa berbeda dengan yang ditampilkan karena menyesuaikan dengan regulasi di Indonesia.**

Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.

Penawaran Harga Spesial
08112039555

- Outdoor AP
- Wi-Fi 7
- 6.45 Gbps device rate
- Dual-radio
- 130 access users recommended
- Max. 1024 access users
- 30 dBm transmit power
- 250 m optimal coverage distance

www.citraweb.com

CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com





www.citraweb.com

Spesifikasi

Model	AP772E
Wi-Fi standard	2.4 GHz: 802.11b/g/n/ax/be 5 GHz:802.11a/n/ac/ac Wave 2/ax/be
Installation Type	Wall,Pole
Optimal Signal Distance (m)	250
Max Number of Access Users	1024
Recommended Number of Access Users	130
Device Rate	6.45 Gbps
Maximum number of physical ports on the entire device	1x 2.5GE (RJ45) 100M/1000M/2500M auto-sensing 1x 10G optical (SFP+), 1G/2.5G/10G auto-sensing 1 x USB port
Radio number	2
Maximum channel bandwidth [MHz]	Radio 0 (2.4 GHz): 40 MHz Radio 1 (5 GHz): 160 MHz
Maximum transmit power	2.4 GHz: 25 dBm/chain 28 dBm (combined power) 5 GHz: 24 dBm/chain 30 dBm (combined power)
MIMO spatial streams	Radio 0 (2.4 GHz): 2x2 Radio 1 (5 GHz): 4x4
Maximum power consumption [W]	20.4 (excluding USB)
Input voltage range [V]	DC: 43.2 V to 57.6 V PoE: 802.3bt/at/af

Dimensions without packaging (H x W x D) [mm(in.)]	220 mm x 250 mm x 77 mm (8.66 in. x 9.84 in. x 3.03 in.)
Long-term operating temperature [°C(°F)]	–40°C to +70°C (–40°F to +158°F) (From 1800 m to 5000 m [5905.51 ft. to 16404.20 ft.], the maximum temperature of the device decreases by 1°C [1.8°F] for every 300 m [984.25 ft.] increase in altitude.)
Long-term operating relative humidity [RH]	Operating humidity: 0% RH to 100% RH Storage humidity: 5% RH to 95% RH (non-condensing)
Radio interface	Built-in directional antennas
Antenna gain	2.4 GHz: 10 dBi/chain (peak value) 10 dBi (combined gain) 5 GHz: 11 dBi/chain (peak value) 10 dBi (combined gain)
Operating frequency band	2.4GHz,5GHz
Ingress protection level (dustproof/waterproof)	IP68
Power supply mode	PoE,DC power adapter

Download Datasheet

** Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat*

URL : https://www.citraweb.com/produk/1548/

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com

www.citraweb.com