CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com

eKitEngine AP772 HUAWEI BE6450 High-Protection Dual - Band Wi-Fi 7 Gigabit Outdoor Access Point



Kode : AP772
Brand : Huawei
Jenis : Wireless Outdoor
Harga : Rp 4.975.000,00

HUAWEI eKitEngine AP772 BE6450 High-Protection Dual - Band Wi-Fi 7 Gigabit Outdoor Access Point adalah *Access Point outdoor* berteknologi Wi-Fi 7 (802.11be) dengan dukungan hingga 6 *spatial streams* untuk menghadirkan performa nirkabel yang cepat dan stabil. Berbekal perlindungan ekstra terhadap air dan debu bersertifikasi IP68 serta proteksi lonjakan listrik yang kuat, AP ini menjadi solusi ideal untuk area luar ruangan berdensitas pengguna tinggi.

***Belum termasuk adaptor dan poe injector**

***Spesifikasi perangkat dijual bisa berbeda dengan yang ditampilkan karena menyesuaikan dengan regulasi di Indonesia.**

Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.

Penawaran **Harga Spesial**
08112039555

- **Outdoor AP**
- **Wi-Fi 7**
- **6.45 Gbps device rate**
- **Dual-radio**
- **130 access users recommended**
- **Max. 1024 access users**
- **30 dBm transmit power**
- **140 m optimal coverage distance**
- **Omnidirectional antenna**

www.citraweb.com





www.citraweb.com

Spesifikasi

Model	AP772
Wi-Fi standard	2.4 GHz: 802.11b/g/n/ax/be 5 GHz:802.11a/n/ac/ac Wave 2/ax/be
Installation Type	Wall,Pole
Optimal Signal Distance (m)	140
Max Number of Access Users	1024
Recommended Number of Access Users	130
Device Rate	6.45 Gbps
Maximum number of physical ports on the entire device	1x 2.5GE (RJ45) 100M/1000M/2500M auto-sensing 1x 10G optical (SFP+), 1G/2.5G/10G auto-sensing 1 x USB port
Radio number	2
Maximum channel bandwidth [MHz]	Radio 0 (2.4 GHz): 40 MHz Radio 1 (5 GHz): 160 MHz
Maximum transmit power	2.4 GHz: 25 dBm/chain 28 dBm (combined power) 5 GHz: 24 dBm/chain 30 dBm (combined power)
MIMO spatial streams	Radio 0 (2.4 GHz): 2x2 Radio 1 (5 GHz): 4x4
Maximum power consumption [W]	20.4 (excluding USB)
Input voltage range [V]	DC: 43.2 V to 57.6 V PoE: 802.3bt/at/af

Dimensions without packaging (H x W x D) [mm(in.)]	92 mm x 250 mm x 220 mm (3.62 in. x 9.84 in. x 8.66 in.)
Long-term operating temperature [°C(°F)]	–40°C to +70°C (–40°F to +158°F) (From 1800 m to 5000 m [5905.51 ft. to 16404.20 ft.], the maximum temperature of the device decreases by 1°C [1.8°F] for every 300 m [984.25 ft.] increase in altitude.)
Long-term operating relative humidity [RH]	Operating humidity: 0% RH to 100% RH Storage humidity: 5% RH to 95% RH (non-condensing)
Radio interface	Built-in directional antennas
Antenna gain	2.4 GHz: 5 dBi/chain (peak value) 3 dBi (combined gain) 5 GHz: 5 dBi/chain (peak value) 3 dBi (combined gain)
Operating frequency band	2.4GHz,5GHz
Ingress protection level (dustproof/waterproof)	IP68
Power supply mode	PoE,DC power adapter

Download Datasheet

** Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat*

URL : https://www.citraweb.com/produk/1549/

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com

www.citraweb.com