CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com

TP-LINK EAP650 OMADA AX3000 Ceiling Mount WiFi 6 Access Point



Kode : EAP650
Brand : TP-Link Omada
Jenis : Wireless Indoor
Harga : Rp 1.783.000,00

TP-LINK EAP650 OMADA merupakan perangkat access point **Dual-Band Wi-Fi 6** dengan kecepatan up to 574 Mbps di 2.4GHz dan 2402 Mbps di 5GHz. Dilengkapi dengan 1 port Gigabit Ethernet 802.3at PoE cocok digunakan pada ceiling/wall.

Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.

***Produk ini belum termasuk PoE Adapter.**
***Spesifikasi perangkat dijual bisa berbeda dengan yang ditampilkan karena menyesuaikan dengan regulasi di Indonesia.**

Penawaran Harga Spesial
08112039555

- **Kecepatan WiFi 6 Ultra-Cepat:** Kecepatan simultan 574 Mbps pada pita 2,4 GHz dan 2402 Mbps pada pita 5 GHz menghasilkan total kecepatan WiFi hingga 2976 Mbps.
- **WiFi 6 Efisiensi Tinggi:** Lebih banyak perangkat yang terhubung dapat menikmati kecepatan yang lebih tinggi.
- **Manajemen Cloud Terpusat:** Integrasi Omada SDN mengelola seluruh jaringan secara lokal atau dari cloud melalui antarmuka web (web UI) atau aplikasi Omada.
- **Saluran 160 MHz:** Menggandakan data pada waktu transmisi puncak dalam satu aliran tunggal dengan HE160.
- **Roaming Mulus:** Streaming video dan panggilan suara tidak terpengaruh saat pengguna berpindah lokasi.
- **Omada Mesh:** Memungkinkan konektivitas nirkabel antar *access point* untuk jangkauan yang lebih luas dan penerapan yang fleksibel.
- **Didukung PoE+:** Mendukung catu daya 802.3at PoE+ dan DC (adaptor sudah termasuk) untuk instalasi yang fleksibel.
- **Desain Sangat Tipis:** Desain elegan berukuran 160 mm × 33.6 mm memberikan fleksibilitas yang lebih tinggi.

www.citraweb.com

CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com



www.citraweb.com

Spesifikasi

Model	EAP650
HARDWARE FEATURES	
Interface	1× Gigabit Ethernet (RJ-45) Port (supports IEEE802.3at PoE)
Button	Reset
Power Supply	• 802.3at PoE • 12V / 1.2 A DC (Power Adapter included) • 48V Passive PoE
Max. Power Consumption	14.6 W
Dimensions (W x D x H)	6.3 × 6.3 × 1.3 in (160 × 160 × 33.6 mm)
Antenna	Internal Omni • 2.4 GHz: 2× 3 dBi • 5 GHz: 3× 5 dBi
Bluetooth	V5.2
Mounting	• Ceiling /Wall Mounting (Kits included) • Junction Box Mounting
WIRELESS FEATURES	
Coverage	1500 ft² (140m²)
Concurrent Clients	250+
Wireless Standards	IEEE 802.11ax/ac/n/g/b/a

CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com

Frequency	5 GHz and 2.4 GHz
Signal Rate	• 5 GHz: Up to 2402 Mbps • 2.4 GHz: Up to 574 Mbps
Transmission Power	• CE: <20 dBm(2.4 GHz, EIRP) <23 dBm(5 GHz, Band1 & Band2, EIRP) <27 dBm(5 GHz, Band3, EIRP) • FCC: <24 dBm (2.4 GHz) <25 dBm (5 GHz)
Wireless Functions	• 1024-QAM • 4× Longer OFDM Symbol • OFDMA • Multiple SSIDs (Up to 16 SSIDs, 8 for each band) • Enable/Disable Wireless Radio • Automatic Channel Assignment • Transmit Power Control (Adjust Transmit Power on dBm) • QoS(WMM) • MU-MIMO • HE160 (160 MHz Bandwidth) • Seamless Roaming • Omada Mesh • Band Steering • Load Balance • Airtime Fairness • Beamforming • Rate Limit • Reboot Schedule • Wireless Schedule • Wireless Statistics based on SSID/AP/Client
Wireless Security	• Captive Portal Authentication • Access Control • Wireless Mac Address Filtering • Wireless Isolation Between Clients • SSID to VLAN Mapping • Rogue AP Detection • 802.1X Support • WPA-Personal/Enterprise, WPA2-Personal/Enterprise, WPA3-Personal/Enterprise
Certification	CE, FCC
Package Content	• EAP650 • Ceiling/Wall Mounting Kits • Installation Guide
Environment	• Operating Temperature: 0-40 deg (32–104 deg) • Storage Temperature: -40-70 deg (-40–158 deg) • Operating Humidity: 10-90% RH non-condensing • Storage Humidity: 5-90% RH non-condensing

www.citraweb.com

** Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat*

URL : https://www.citraweb.com/produk/1583/

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com

www.citraweb.com