CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com

TP-LINK EAP115 OMADA 300Mbps Wireless N Ceiling Mount Access Point



Kode : EAP115
Brand : TP-Link Omada
Jenis : Wireless Indoor
Harga : Rp 427.000,00

TP-LINK EAP115 OMADA merupakan perangkat access point **Single-Band** 2.4GHz dengan kecepatan up to 300Mbps. Access point ini memiliki 1 port Fast Ethernet (Support IEEE802.3af PoE).

Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.

***Produk ini belum termasuk PoE Adapter.**
***Spesifikasi perangkat dijual bisa berbeda dengan yang ditampilkan karena menyesuaikan dengan regulasi di Indonesia.**

Penawaran Harga Spesial
08112039555

- **Terintegrasi ke dalam Omada SDN** : Manajemen Cloud Terpusat, dan Pemantauan Cerdas.
- **Manajemen Terpusat** : Akses cloud dan aplikasi Omada untuk kenyamanan maksimal dan manajemen yang mudah.
- **Dukungan PoE** : Mendukung Power over Ethernet (802.3af) untuk kemudahan pemasangan.
- **Pemasangan Mudah** : Desain pemasangan sederhana untuk memudahkan pemasangan ke dinding atau langit-langit.
- **Jaringan Tamu Aman** : Dilengkapi dengan berbagai pilihan otentikasi (SMS/Facebook Wi-Fi/Voucher, dll.) dan teknologi keamanan nirkabel yang melimpah.
- **Penyeimbangan Beban** : Batasi jumlah pengguna pada setiap titik akses dan singkirkan perangkat dengan penerimaan sinyal lemah untuk menjaga agar Wi-Fi Anda tetap berjalan pada kinerja puncak.
- **Penjadwalan** : Secara otomatis melakukan reboot titik akses dan menghidupkan atau mematikan Wi-Fi pada waktu yang Anda tetapkan.

www.citraweb.com

CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com



Spesifikasi

Model	EAP115
HARDWARE FEATURES	
Interface	1× Fast Ethernet (RJ-45) Port (Support IEEE802.3af PoE)
Button	Reset
Power Supply	802.3af PoE or external 9VDC/0.6A power supply
Max. Power Consumption	2.8 W
Dimensions (W x D x H)	7.5×6.7×1.2 in (189.5×170.5×29.7mm)
Antenna	Internal 2× 4 dBi Omni
Mounting	Ceiling / Wall Mounting (Kits Included)
WIRELESS FEATURES	
Coverage	60 ft² (60m²)
Concurrent Clients	100+
Wireless Standards	IEEE 802.11n, IEEE 802.11g, IEEE 802.11b
Frequency	2.4 - 2.4835 GHz
Signal Rate	• 11n: Up to 300Mbps(dynamic) • 11g: Up to 54Mbps(dynamic) • 11b: Up to 11Mbps(dynamic)

www.citraweb.com

Reception Sensitivity	• 300M: -71dBm@10% PER • 150M: -75dBm@10% PER • 54M: -78dBm@10% PER • 11M: -93dBm@8% PER • 6M: -92dBm@10% PER • 1M: -96dBm@8% PER
Wireless Functions	• Multiple SSIDs (Up to 8 SSIDs) • Enable/Disable Wireless Radio • Automatic Channel Assignment • Transmit Power Control (Adjust Transmit Power on dBm) • QoS(WMM) • Rate Limit • Reboot Schedule • Wireless Schedule • Wireless Statistics based on SSID/AP/Client
Wireless Security	• Captive Portal Authentication • Access Control • Wireless MAC Address Filtering • Wireless Isolation Between Clients • SSID to VLAN Mapping • Rogue AP Detection • 802.1X Support • 64/128/152-bit WEP / WPA / WPA2-Enterprise,WPA-PSK / WPA2-PSK
Transmission Power	• CE: ≤19 dBm (EIRP) • FCC: ≤21 dBm
Certification	CE, FCC
Package Content	• 300Mbps Wireless N Ceiling Mount Access Point EAP115 • Mounting Kits • Installation Guide
Environment	• Operating Temperature: 0 - 40 °C (32 - 104 °F) • Storage Temperature: -40 - 70 °C (-40 - 158 °F) • Operating Humidity: 10%–90% non-condensing • Storage Humidity: 5%–90% non-condensing

www.citraweb.com

Download Datasheet

* *Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat*

URL : https://www.citraweb.com/produk/1589/

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com