CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com

TP-LINK TL-SG1008MP OMADA 8-Port Gigabit PoE+ Unmanaged Switch

Kode : TL-SG1008MP
Brand : TP-Link Omada
Jenis : Switch Unmanaged POE
Harga : Rp 1.454.000,00

TP-LINK TL-SG1008MP OMADA merupakan unmanaged switch yang dilengkapi 8 port Gigabit PoE+ dengan standard IEEE 802.3af/at yang mampu memberikan daya PoE hingga 153W.

Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.

Penawaran Harga Spesial
08112039555

- **8 port RJ45 10/100/1000Mbps.**
- **Dilengkapi dengan 8 port yang mendukung PoE+ untuk mentransfer data dan daya melalui satu kabel.**
- **Kompatibel dengan perangkat yang sesuai dengan standar IEEE 802.3af/at, memperluas jaringan rumah dan kantor.**
- **Teknologi hemat energi yang inovatif mengurangi konsumsi daya hingga 75%.**
- **Mendukung standar PoE+ dengan total daya 153W dan hingga 30W per port.**
- **Desain plug and play, tidak memerlukan konfigurasi.**

www.citraweb.com

BACK VIEW

CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com

Spesifikasi

Model	TL-SG1008MP
HARDWARE FEATURES	
Interface	8 10/100/1000Mbps RJ45 Ports AUTO Negotiation/AUTO MDI/MDIX
Fan	1
Physical Security Lock	No
Power Supply	100-240VAC, 50/60Hz
PoE Ports (RJ45)	Standard: 802.3af/at compliant PoE+ Ports: 8 Ports Power Supply: 153W
Dimensions (W x D x H)	11.6*7.1*1.7 in. (294*180*44 mm)
Max. Power Consumption	• 8.77 W(220V/50Hz. no PD connected) • 172.49 W(110V/60Hz. with 153W PD connected)
Max. Heat Dissipation	• 29.91 BTU/h(no PD connected) • 588.19 BTU/h(with 153W PD connected)
Jumbo Frame	16 KB
Switching Capacity	16Gbps
MAC Address Table	4K
Advanced Features	• Compatible With IEEE 802.3af/at Compliant PDs • Priority Function • Mac Address Auto-Learning And Auto-Aging • IEEE802.3x Flow Control for Full-Duplex Mode and Backpressure for Half-Duplex Mode • Extend Mode Button (Ports 1–2, Up to 250 m PoE power supply and data transmission) • PoE Auto Recovery (Ports 1-8)
OTHERS	
Certification	CE, FCC
Package Content	TL-SG1008MP Power Cord Installation Guide Rackmount Kit Rubber Feet

www.citraweb.com

Environment	• Operating Temperature: 0–50 C (32–122 F) • Storage Temperature: -40–70 C (-40–158 F) • Operating Humidity: 10–90% RH non-condensing • Storage Humidity: 5–90% RH non-condensing

Download Datasheet

** Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat*

URL : https://www.citraweb.com/produk/1691/

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com

www.citraweb.com