CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com

TP-LINK TL-SG1005LP OMADA 5-Port Gigabit Desktop Unmanaged Switch with 4-Port PoE+

Kode : TL-SG1005LP
Brand : TP-Link Omada
Jenis : Switch Unmanaged POE
Harga : Rp 430.000,00

TP-LINK TL-SG1005LP OMADA merupakan unmanaged switch yang dilengkapi 5 port Gigabit dengan 4 port support PoE+ standard IEEE 802.3af/at yang mampu memberikan daya PoE hingga 40W.

Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.

Penawaran Harga Spesial
08112039555

- **5 port RJ45 10/100/1000 Mbps**
- **Dengan empat port PoE+, mentransfer data dan daya melalui satu kabel tunggal.**
- **Kompatibel dengan PD yang sesuai dengan standar IEEE 802.3af/at.**
- **QoS 802.1p/DSCP memungkinkan kelancaran lalu lintas yang sensitif terhadap latensi.**
- **Mendukung daya PoE hingga 30 W untuk setiap port PoE.**
- **Mendukung daya PoE hingga 40 W untuk semua port PoE.**
- **Plug-and-Play, tidak perlu konfigurasi dan instalasi.**

Spesifikasi

Model	TL-SG1005LP
HARDWARE FEATURES	
Interface	• 5× 10/100/1000Mbps RJ45 Ports • AUTO Negotiation • AUTO MDI/MDIX
Fan	Fanless
Power Supply	External Power Adapter (Output: 53.5 VDC / 0.81 A)
PoE Ports (RJ45)	• Standard: 802.3 af/at compliant • PoE Ports: Ports 1–4 • Power Supply: 40 W

www.citraweb.com

Dimensions (W x D x H)	3.9×3.9×1.0 in (99.8×98×25 mm)
Max. Power Consumption	• 4.12 W (220/50 Hz. no PD connected) • 47.5 W (220/50 Hz. with 40 W PD connected)
Max. Heat Dissipation	• 14.05 BTU/h (no PD connected) • 161.98 BTU/h (with 40 W PD connected)
Jumbo Frame	16 KB
Switching Capacity	10 Gbps
Packet Forwarding Rate	7.44 Mpps
MAC Address Table	2K
Advanced Features	• Compatible With IEEE 802.3af/at Compliant PDs • Mac Address Auto-Learning And Auto-Aging • IEEE 802.3x Flow Control • 802.1p/DSCP QoS • IGMP Snooping
OTHERS	
Certification	CE, FCC
Package Content	TL-SG1005LP Power Adapter Installation Guide
Environment	• Operating Temperature: 0–40 C (32–104 F) • Storage Temperature: -40–70 C (-40–158 F) • Operating Humidity: 10–90% RH non-condensing • Storage Humidity: 5–90% RH non-condensing

Download Datasheet

* *Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat*

URL : https://www.citraweb.com/produk/1694/

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com

www.citraweb.com