

TP-LINK TL-SL1311P OMADA 8-Port PoE+ 10/100Mbps 3-Port Gigabit Desktop Unmanaged Switch

Kode : TL-SL1311P

Brand : TP-Link Omada

Jenis : Switch Unmanaged POE

Harga : Rp 648.000,00



TP-LINK TL-SL1311P OMADA merupakan unmanaged switch yang dilengkapi 8 port PoE+ 10/100 Mbps RJ45, 2 port Gigabit RJ45 dan 1 port Gigabit SFP. Switch ini mampu memberikan daya PoE hingga 65W.

Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.

Penawaran Harga Spesial

 **08112039555**

- 8 port RJ45 10/100 Mbps, 2 port RJ45 Gigabit, 1 port SFP Gigabit.
- 8 port PoE+ mentransfer data dan daya melalui kabel terpisah.
- Kompatibel dengan PD yang sesuai dengan standar IEEE 802.3af/at.
- Mendukung daya PoE hingga 30 W untuk setiap port PoE.
- Mendukung daya PoE hingga 65 W untuk 8 port PoE.
- Mode Isolasi memungkinkan pemisahan lalu lintas klien dengan sekali klik untuk keamanan dan kinerja yang lebih tinggi.
- PoE Auto Recovery menjamin pengoperasian perangkat PoE yang stabil dengan secara otomatis melakukan reboot perangkat PD yang terputus atau tidak responsif.
- Desain tanpa kipas mengurangi konsumsi daya dan bekerja tanpa suara di lokasinya.
- Plug-and-Play tanpa perlu konfigurasi.

BACK VIEW



Spesifikasi

Model	TL-SL1311P
HARDWARE FEATURES	
Interface	<ul style="list-style-type: none"> • 8x 10/100 Mbps 802.3af/at PoE+ Ports, 2x Gigabit RJ45 Ports, 1x Gigabit SFP Port • AUTO Negotiation • AUTO MDI/MDIX
Fan	Fanless
Physical Security Lock	Yes
Power Supply	External Power Adapter (Output: 53.5 VDC / 1.31 A)
PoE Ports (RJ45)	<ul style="list-style-type: none"> • Standard: 802.3 af/at compliant • PoE Ports: Ports 1-8 • Power Supply: 65 W
Dimensions (W x D x H)	8.2 x 4.9 x 1.0 in (209 x 126 x 26 mm)
Max. Power Consumption	<ul style="list-style-type: none"> • 5.61 W (220 V/50 Hz. no PD connected) • 77.32 W (110 V/50 Hz. with 65 W PD connected)
Max. Heat Dissipation	<ul style="list-style-type: none"> • 19.13 BTU/h (no PD connected) • 263.7 BTU/h (with 65 W PD connected)
Jumbo Frame	16 KB
Switching Capacity	7.6 Gbps
Packet Forwarding Rate	5.6544 Mpps
MAC Address Table	2K

Advanced Features	<ul style="list-style-type: none"> • Compatible With IEEE 802.3af/at Compliant PDs • Extend Mode Button (Ports 1-4 and Ports 1-8, Up to 250 m PoE power supply and data transmission) • Isolation Mode Button (Ports 1-8) • PoE Auto Recovery Button (Ports 1-8) • Mac Address Auto-Learning and Auto-Aging • IEEE802.3x Flow Control For Full-Duplex Mode And Backpressure for Half-Duplex Mode
OTHERS	
Certification	CE, FCC
Package Content	<ul style="list-style-type: none"> • TL-SL1311P • Power Adapter • Installation Guide
Environment	<ul style="list-style-type: none"> • Operating Temperature: 0-40 C (32-104 F) • Storage Temperature: -40-70 C (-40-158 F) • Operating Humidity: 10-90% RH non-condensing • Storage Humidity: 5-90% RH non-condensing

[Download Datasheet](#)

* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

URL : <https://www.citraweb.com/produk/1700/>

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com