CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com

TP-LINK TL-SF1009P OMADA 9-Port 10/100Mbps Desktop Unmanaged Switch with 8-Port PoE+

Kode : TL-SF1009P
Brand : TP-Link Omada
Jenis : Switch Unmanaged POE
Harga : Rp 586.000,00

TP-LINK TL-SF1009P OMADA merupakan unmanaged switch yang dilengkapi 9 Port 10/100 Mbps RJ45 (8 Port support 802.3af/at PoE+). Switch ini mampu memberikan daya PoE hingga 65W.

Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.

Penawaran Harga Spesial
08112039555

- **9 port RJ45 10/100 Mbps**
- **8 port PoE+ mentransfer data dan daya melalui kabel terpisah.**
- **Kompatibel dengan PD yang sesuai dengan standar IEEE 802.3af/at.**
- **Mendukung daya PoE hingga 30 W untuk setiap port PoE.**
- **Mendukung daya PoE hingga 65 W untuk 8 port PoE**.
- **Mode Prioritas memastikan prioritas tinggi pada port 1–2 untuk menjamin kualitas aplikasi sensitif.**
- **Mode Isolasi memungkinkan pemisahan lalu lintas klien dengan sekali klik untuk keamanan dan kinerja yang lebih tinggi.**
- **Pasang dan mainkan, tanpa perlu konfigurasi dan instalasi.**

Spesifikasi

Model	TL-SF1009P
HARDWARE FEATURES	
Interface	• 9× 10/100 Mbps RJ45 Ports (8× 10/100 Mbps 802.3af/at PoE+ ports) • AUTO Negotiation • AUTO MDI/MDIX
Fan	Fanless
Physical Security Lock	Yes
Power Supply	External Power Adapter (Output: 53.5VDC / 1.31A)

www.citraweb.com

PoE Ports (RJ45)	• Standard: 802.3 af/at compliant • PoE Ports: Ports 1–8 • Power Supply: 65 W
Dimensions (W x D x H)	6.7 × 3.9 × 1.1 in (171 × 98 × 27 mm)
Max. Power Consumption	• 3.6 W (220/50 Hz. no PD connected) • 77.08 W (220/50 Hz. with 65 W PD connected)
Max. Heat Dissipation	• 12.28 BTU/h (no PD connected) • 262.84 BTU/h (with 65 W PD connected)
Jumbo Frame	2 KB
Switching Capacity	1.8 Gbps
Packet Forwarding Rate	1.3392 Mpps
MAC Address Table	2K
Advanced Features	• Compatible With IEEE 802.3af/at Compliant PDs • Extend Mode Button (Ports 1–4 and Ports 1–8, Up to 250 m PoE power supply and data transmission) • Priority Mode Button (Ports 1–2) • Isolation Mode Button (Ports 1–8) • Mac Address Auto-Learning and Auto-Aging • IEEE802.3x Flow Control For Full-Duplex Mode And Backpressure for Half-Duplex Mode
OTHERS	
Certification	CE, FCC
Package Content	• TL-SF1009P • Power Adapter • Installation Guide
Environment	• Operating Temperature: 0–40 C (32–104 F) • Storage Temperature: -40–70 C (-40–158 F) • Operating Humidity: 10–90% RH non-condensing • Storage Humidity: 5–90% RH non-condensing

www.citraweb.com

Download Datasheet

** Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat*

URL : https://www.citraweb.com/produk/1701/

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com