

# Embedded RB433AH (A+G) 20dbi - rev2



**Kode** : EM433AH-5X-r2

**Brand** : Discontinued

**Jenis** : Discontinued

**Harga** : Rp 3.445.000,00

RouterBoard 433AH (Lisensi Level 4CF-AP) dengan Wireless MiniPCI yang dipadukan dengan embedded antenna 5GHz 20dbi, menghasilkan unit wireless yang ringkas. Sudah termasuk adaptor 24V dan PoE.

## Detail Barang:

- Routerboard 433AH dengan outdoor box dan embedded antenna 5GHz
- 1 port ethernet (1 untuk PoE)
- 1 slot minipci
- 1 buah Atheros MiniPCI Wireless 802.11a+b+g 54Mbps 2.4/5GHz 350mW
- 1 Insulator Ethernet
- Power Adaptor 24V
- Power over Ethernet Splitter
- Pole mounting bracket
- Lisensi Mikrotik RouterOS AP - Level 5 /CF

| Spesifikasi RB433AH |               |
|---------------------|---------------|
| Product Code        | RB433AH       |
| Architecture        | MIPS-BE       |
| CPU                 | AR7161 680MHz |
| Current Monitor     | No            |
| Main Storage/NAND   | 64MB          |
| RAM                 | 128MB         |
| SFP Ports           | 0             |
| LAN Ports           | 3             |
| Gigabit             | No            |
| Switch Chip         | 1             |
| MiniPCI             | 3             |
| Integrated Wireless | No            |

|                    |               |
|--------------------|---------------|
| MiniPCle           | 0             |
| SIM Card Slots     | No            |
| USB                | No            |
| Memory Cards       | 1             |
| Memory Card Type   | MicroSD       |
| Power Jack         | 10-28V        |
| 802.3af Support    | No            |
| POE Input          | 10-28V        |
| POE Output         | No            |
| Serial Port        | DB9/RS232     |
| Voltage Monitor    | No            |
| Temperature Sensor | No            |
| Dimentions         | 150mm x 105mm |
| Operating System   | RouterOS      |
| Temperature Range  | -30C .. +60C  |
| RouterOS License   | Level5        |

**Embedded Antenna & Enclosure Specifications:**

- **Frequency:** 5400-5850MHz
- **Antenna Gain:** 20 dbi
- **VSWR:** 1.5:1
- **Impedance:** 50 Ohm
- **Operating Temperature:** -45 to 80 deg C
- **Beam Width (H):** 18 Deg
- **Beam Width (V):** 18 Deg
- **Dimmentions (outer):** 280mm (L) x 265mm (w) x 95mm (d)
- **Weight:** 2.85 kg

