

Cambium Networks ePMP Force 300-25 Subscriber Module 5GHz



Kode : ePMP-FORCE-300-25

Brand : Cambium

Jenis : Wireless PTP


Harga : Rp 3.800.000,00

ePMP Force 300-25

Cambium Networks' ePMP Force 300-25 is designed to operate in high interference environments and provides superior throughput of over 500 Mbps of real user data.

***Spesifikasi perangkat dijual bisa berbeda dengan yang ditampilkan karena menyesuaikan dengan regulasi di Indonesia.**

Penawaran Harga Spesial

 08112039555

The High-gain ePMP Force 300-25 802.11AC Wave 2 solution provides 500+ Mbps peak throughput, always-on spectrum analysis, and local WiFi management.

| SPECTRUM | |
|----------------------------------|--|
| Channel Spacing | Configurable in 5 MHz increments |
| Frequency Range regulations.) | Wide Band Operation 4910 - 5970 MHz (Note: Allowable frequencies and bands are dictated by individual country) |
| Channel Width | 20 40 80 MHz |
| | |
| INTERFACE | |
| MAC (Media Access Control) Layer | Cambium |
| Proprietary Physical Layer | 2x2 MIMO/OFDM |
| Ethernet Interfaced | 10/100/1000 BaseT, Compatible with Cambium PoE & Standard PoE pinouts |
| Protocols Used | IPv4/IPv6 (Dual Stack), UDP, TCP, ICMP, SNMPv2c, NTP, STP, IGMP, SSH |
| Network Management | IPv4/IPv6, HTTPs, SNMPv2c, SSH, Cambium Networks CnMaestro™ |

| | |
|---|--|
| VLAN | 802.1Q with 802.1p priority |
| PERFORMANCE | |
| ARQ | Yes |
| Nominal Receive Sensitivity (w/FEC) @20 MHz Channel | MCS0 = -87 dBm to MCS8 (256 QAM-3/4) = -63 dBm (per chain) |
| Nominal Receive Sensitivity (w/FEC) @40 MHz Channel | MCS0 = -85 dBm to MCS9 (256QAM-5/6) = -59 dBm (per chain) |
| Nominal Receive Sensitivity (w/FEC) @80 MHz Channel | MCS0 = -82 dBm to MCS9 (256QAM-5/6) = -56 dBm (per chain) |
| Modulation Levels (Adaptive) | MCS0(BPSK)to MCS9 (256QAM5/6) |
| Transmit Power Range | 0 to +27 dBm (combined, to regional EIRP limit) (1 dB interval) |
| PHYSICAL | |
| Surge Suppression | 1 Joule Integrated (C000000L065A - 30V Gigabit surge suppressor is recommended for optimum protection) |
| Environmental | IP55 |
| Temperature | -30°C to +60°C (-22°F to +140°F) |
| Weight | 2.4 kg (5.3 lbs) |
| Wind Survival | 180 km/hour (112 mi/hour) |
| Dimensions (Dia x Depth) | 47 cm x 31 cm (18.5 in x 12.2 in) |
| Pole Diameter Range | 6.4 cm - 7.6 cm (2.5 in - 3 in) |
| Power Consumption | 12 Watts |
| Input Voltage | 30 Volts |
| SECURITY | |
| Encryption | 128-bit AES (CCMP mode) |

| | |
|--|-----------------|
| ANTENNA SPECIFICATIONS 5 GHZ SPECIFICATION | |
| Frequency Range | 4910 - 5970 MHz |
| Antenna Type | Dish |
| Peak Gain | 25 dBi |

| | |
|-------------------------|--------------|
| 3dB Beamwidth-Azimuth | 6-10 degrees |
| 3dB Beamwidth-Elevation | 6-10 degrees |
| Front-To-Back Isolation | 25 dB |
| Cross Polarization | 20 dB |

* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

URL : <https://www.citraweb.com/produk/720/>

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com

www.citraweb.com