

Cambium Networks cnPilot e410 Access Point

Kode : cnPilot-e410

Brand : Cambium

Jenis : Wireless Indoor

Harga : Rp 2.662.000,00



cnPilot e410

The plenum-rated cnPilot e410 with 2x2 MU-MIMO packs a max transmit power of 25 dBm and channels up to 80MHz wide on 5 GHz - offering more flexibility than ever for both coverage and capacity.

***Untuk pembelian produk promo ini tidak termasuk poe adaptor
 Jika membutuhkan poe adaptor bisa menggunakan [RG-POE-A15](#)**

***Spesifikasi perangkat dijual bisa berbeda dengan yang ditampilkan karena menyesuaikan dengan regulasi di Indonesia.**

Penawaran Harga Spesial

 08112039555

| ACCESS POINT SPECIFICATIONS | |
|-----------------------------|--|
| Radios | 1 x 5 GHz radio (802.11 a/n/ac Wave 2), 2x2 1 x 2.4 GHz (802.11 b/g/n), 2X2 SU-MIMO / MU-MIMO: 2 streams |
| Wi-Fi | 802.11 a/b/g/n/ac |
| Range | 180 m (650 Ft) |
| Concurrent Clients | 256 |
| Max Data Rates | 1.3 Gbps (1,267 Mbps) |
| SSID | 32 SSIDs (16 per radio) |
| Antenna gain | 5.24 dBi (2.4 GHz) , 5.47 dBi (5 GHz) |
| Multi-Hop Mesh | Yes. Supported on Indoor & Outdoor access points. |
| | Mesh auto-recovery supported |

| | |
|------------------|---|
| Polarization | Dual-linear |
| Antenna Coverage | Omni (360°) |
| Ethernet Ports | One (1) x 1 Gigabit Ethernet (10/100/1000 Mbps) |
| Frequency bands | 2.4 GHz: 2400-2484 MHz |
| | 5 GHz: 5150-5850 MHz with DFS band support |
| Power Supply | Standard 802.3af injector (supplied) or any PoE switch |
| Power Consumed | 11.5W (max) |
| Dimensions | 180 x 180 x 42 mm (18 x 18 x 4.2 cm) |
| Weight | 384grams (0.384kg) |
| Temperature | 0°C to +50°C |
| LED | Single LED window with tri color (Amber, Blue, Green) display |
| Max EIRP | 2.4 GHz: 29.50 dBm , 5 GHz: 30 dBm |
| Physical Lock | Kensington key hole |

| WI-FI FEATURES | |
|-----------------------|--|
| Controller modes | <ul style="list-style-type: none"> • Autonomous Controller-less operations (E.g.: roaming) • Cloud Managed • On-premise virtualized controller |
| Secure WLAN | WPA-TKIP, WPA2 AES, 802.1x |
| | 802.11w (Protected Management Frames) |
| Hotspot 2.0/Passpoint | Yes |
| Captive Portal/ | • cnMaestro Controller |
| Guest Access | <ul style="list-style-type: none"> • Stand-alone AP based • Redirection to external RADIUS Server • Active Directory Integration |
| Authentication | Secure Web page, RADIUS based 802.1x including EAP-SIM/AKA, |
| | EAP-PEAP, EAP-TTLS, and EAP-TLS |
| | MAC authentication (local database or External RADIUS server) |
| Accounting | Yes. Supports RADIUS based accounting to multiple AAAs |
| Scheduled SSID | Turn SSID ON/OFF on a daily/weekly/time of day basis |
| VLAN | Dynamic VLAN assignment from RADIUS server. |

| | |
|-------------------|---|
| | VLAN per SSID per user, VLAN load balancing |
| Data Limiting | Dynamic rate limiting of client traffic per SSID & per client |
| Subscriber QoS | WMM |
| Client Isolation | Yes |
| Controller-Less | Yes. 802.11r, Opportunistic Key Caching supports Enhanced roaming |
| Fast Roaming | Disconnect for sticky clients |
| Airtime Fairness | Yes |
| Meshing | Multi-hop meshing supported (3) |
| ACS: Automatic | Yes. Set at start or run periodically |
| Channel Selection | |
| NAT | Yes |
| DHCP Server | Yes |
| Firewall | Yes. NAT logging |
| ACL, DNS-ACL | Yes. L2, L3 or DNS based access control |
| Band Steering | Yes |
| Band Balancing | |
| Airtime Fairness | Yes |
| Tunneling | • L2TP • L2GRE • PPPoE |
| Tools | • Packet capture • IP connectivity • Wi-Fi analyzer |
| | • Wireless Sniffer • Tech support (logs) |
| Services | NTP server config |
| | Syslog servers |
| | SNMP traps support |
| | DNS proxy |
| | cnPilot's critical resource service |
| | awareness feature reacts to the health |
| | of an external Gateway or AAA and |
| | turns SSID ON/OFF |
| APIs | Presence Locationing API |
| Certifications | Wi-Fi Alliance 802.11 a/b/g/n/ac, Passpoint 2.0 |
| | FCC, ETSI, CE, EN 60601-1-2 (Medical EMC) |

| | |
|--|------------------------------|
| | IEC62368 UL2043 Plenum rated |
|--|------------------------------|

* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

URL : <https://www.citraweb.com/produk/722/>

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com

www.citraweb.com