

Cambium Networks cnPilot e500 Access Point



Kode : cnPilot-e500

Brand : Discontinued

Jenis : Discontinued

Harga : Rp 7.258.000,00

cnPilot e500 APs feature two Gigabit Ethernet ports and an AUX port capability, enabling outdoor deployment anywhere with additional power available for another backhaul radio, security camera, or other additional equipment.

Penawaran Harga Spesial

 08112039555

| Access Point - Specifications | |
|-------------------------------|---|
| FREQUENCY BANDS | 2.4 GHz: 2.4 - 2.484 GHz |
| | Channels 1 - 13 (ETSI/CE), |
| | Channels 1 - 11 (US) |
| | 5 GHz: 5.15 - 5.85 GHz |
| | Channels 36 - 165. 5 GHz channels are country dependent |
| SSID SECURITY | WPA-2 (802.11i): WPA2-Enterprise (802.1x/EAP) & WPA2-Preshared-keys, Open |
| MAX SSIDS | 16 |
| MAX CONCURRENT CLIENTS | 256 |
| MAX RANGE | 275m (900 Ft); Actual range will vary depending on local RF conditions and client capability |
| MAX DATA RATES | 1.01 Gbps |
| ETHERNET PORTS | Dual Gigabit Ethernet ports (2 x 10/100/1000Base-T) |
| ANTENNA | Linear vertically polarized 2x2 MIMO Integrated Omni (360 °) |
| ANTENNA GAIN | 5 dBi |
| POWER SUPPLY | 56V/30W Gigabit passive PoE injector |
| POE OUT | Aux port: capable of 802.3af Power out or Canopy power (for supported Cambium ePMP or PMP450 SMs) |

| | |
|-----------------------|---|
| TRANSMIT POWER | 29dBm @ 2.4GHz |
| | 28dBm @ 5 GHz |
| POWER CONSUMED | Typical: 8W Max: 12.95W (no auxiliary device connected) |
| DIMENSIONS (CM) | 30 x 20.4 x 6.5 cm (without bracket) |
| WEIGHT | Without bracket: 881 g (0.88 Kg); with Bracket: 1,063 g (1.06 Kg) |
| OPERATING TEMPERATURE | -30 °C ~ 60 °C |
| MOUNTING OPTIONS | Pole mount bracket (included) or wall mount (included) |
| LTE CO-EXISTENCE | Special filter for rejecting interference on 2.4 GHz from adjacent LTE bands 38, 40 |
| PHYSICAL SECURITY | Kensington Lock bracket |
| VISUAL STATUS | Two (2) multi-color LEDs indicating Access Point & cnMaestro connectivity status |

| | |
|-------------------------|--|
| WiFi Features | |
| WIFI DEPLOYMENT OPTIONS | Autonomous Stand-alone operation |
| | Cloud Managed |
| | On-premise controller |
| MESH | Standard 802.11 Meshing (Mesh) between cnPilot APs |
| HOTSPOT CAPTIVE PORTAL | Controller based Hotspot (on cnMaestro) |
| | Stand-alone mode AP based hotspot server. |
| | Also supports hotspot redirection to a 3rd party hotspot server |
| AUTHENTICATION | RADIUS based 802.1x including EAP-SIM/AKA, AP-PEAP, EAP-TTLS, EAP-TLS or Secure |
| | Web page portal based authentication |
| SCHEDULED SSID | Turn SSID ON/OFF on a daily/weekly/time of day basis |
| AAA | Authentication to RADIUS AAA per SSID (Active/Standby) |
| GUEST ACCESS | Yes |
| CLIENT DATA LIMITING | Uplink & Downlink rate limiting per SSID |
| ACCOUNTING | Yes. Supports RADIUS based accounting to multiple AAAs |
| SUBSCRIBER QOS | WMM |
| SUBSCRIBER HANDLING | Dynamic VLAN assignment from RADIUS server |
| CLIENT ISOLATION | Yes |
| FAST ROAMING | Controller-less fast roaming supported including 802.11r and Opportunistic Key Caching |

| | |
|-----------------------------|---|
| AUTOMATIC CHANNEL SELECTION | Yes |
| NAT | Yes (Network Address Translation) |
| DHCP SERVER | Yes |
| FIREWALL | Yes |
| BAND STEERING | Yes. Steers 802.11n and 802.11ac clients towards the higher throughput 5 GHz band |
| LOAD BALANCING | Yes |

* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

URL : <https://www.citraweb.com/produk/724/>

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com

www.citraweb.com